



# SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896

Fax: 613-394-4101 email: sales@electrocables.com

Mailing: P.O. Box 276, Trenton, ON K8V 5R5

www.electrocables.com

23-Jan-2026

Product Number : **5151804BPV6.10R.300**

RoHS

Overall Shielded Cable 4/C 18/7 AWG SBC

600V 75°C CSA-C/US CMP

PVC Insulation, O/A Shield & O/A Drain

PVC Jacket

## General Specification of Product :

Final Diameter : 0.190 inches 4.826 mm

Total Cable Weight: 55.0 kg/km 37.0 lbs/1000 ft

Conductor : 18 AWG 7 Stranded Bare Copper

Insulation : PVC

Shield : Overall Foil Shield

Drain \ Ground: 24 AWG 7 Stranded Tinned Copper

Colour Code: Black,White,Red,Green

Temp. Range: -20 to 75°C

Min. Bend Radius: 1.3 inches

Twists per Foot 4

Ripcord : RIPCORDER

Outer Jacket : PVC

Certification and Approvals : CSA C22.2 No. 214/UL 444, CSA C22.2 No. 210

## Print Notes :

Standard Print : CSA-C/US CMP LL61365 75°C OR CSA AWM II A/B 75°C 600V FT6 4/C 18  
AWG ROHS WWW.CERCOCABLE.COM A B C D E F G H I  
J

## Electrical Characteristics :

DC Resistance 25°C: 6.7 Ohms / 1000 ft

Mutual Capacitance : 53.2 pF/ft

Cond to Shield Cap. : 94.3 pF/ft

Impedance : 40 Ohms

All Cables are Canadian Made in Ontario

QMS Registered ISO 9001

Electro Cables Inc. has been manufacturing quality cables for over 35 years.

( All of the above values are approximated to within +/- 10% )

5151804BPV6.10R.300



# SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896

Fax: 613-394-4101 email: [sales@electrocables.com](mailto:sales@electrocables.com)

Mailing: P.O. Box 276, Trenton, ON K8V 5R5

[www.electrocables.com](http://www.electrocables.com)

23-Jan-2026

Inductance. : 1.4 mH/km

All Cables are Canadian Made in Ontario

QMS Registered ISO 9001

Electro Cables Inc. has been manufacturing quality cables for over 35 years.

( All of the above values are approximated to within +/- 10% )

5151804BPV6.10R.300