



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896

Fax: 613-394-4101 email: sales@electrocables.com

Mailing: P.O. Box 276, Trenton, ON K8V 5R5

www.electrocables.com

18-Jul-2023

Product Number : **5152202BPV6**

RoHS

Overall Shielded Cable 2/C 22/7 AWG SBC
CSA-C/US CMP FT6 75°C, CSA 600V AWM
PVC Insulation, PVC Jacket

General Specification of Product :

Final Diameter :	0.124 inches	3.150 mm
Total Cable Weight:	20.0 kg/km	13.4 lbs/1000 ft
Conductor :	22 AWG 7 Strand Bare Copper	
Insulation :	0.008" PVC	
Shield :	Overall Foil Shield	
Drain \ Ground:	24 AWG 7 Strand Tinned Copper Conductor	
Colour Code :	Black,White	
Temp. Range :	-20 to 75°C	
Min. Bend Radius:	0.8 inches	
Twist per Foot:	6	
Ripcord :	RIPCORDER	
Outer Jacket :	PVC	

Certification and Approvals : CSA C22.2 No. 214/UL 444, CSA C22.2 No. 210

Print Notes : Sequentially marked in Meters (0 - infinity)

Standard Print : CSA-C/US CMP LL61365 75°C OR CSA AWM II A/B 75°C 600V FT6 2/C 22 AWG
ROHS WWW.CERCOCABLE.COM A B C D E F G H I J

Electrical Characteristics :

DC Resistance 25°C:	16.9 Ohms / 1000 ft
Mutual Capacitance :	54.8 pF/ft
Cond to Shield Cap. :	101.6 pF/ft
Impedance :	65 Ohms
Inductance. :	1.4 mH/km

All Cables are Canadian Made in Ontario

QMS Registered ISO 9001

Electro Cables Inc. has been manufacturing quality cables for over 35 years.

(All of the above values are approximated to within +/- 10%)

5152202BPV6