



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896

Fax: 613-394-4101 email: sales@electrocables.com

Mailing: P.O. Box 276, Trenton, ON K8V 5R5

www.electrocables.com

10-JUL-2025

Product Number : **5302251TFT4.AH**

RoHS

AT-HOM Shielded Lo-Cap 1/PR 22/7 AWG STC

LO-CAP FPO Insulation, Overall Foil Shield & Overall Drain, DARK ORANGE

PVC Jacket

General Specification of Product :

Final Diameter : 0.172 inches 4.369 mm

Total Cable Weight: 14.0 kg/km 9.4 lbs/1000 ft

Conductor : 22 AWG 7 Stranded Tinned Copper

Insulation : 0.020 FPO

Shield : Overall Foil Shield

Drain \ Ground: 24 AWG 7 Stranded Tinned Copper

Colour Code: Blk paired with Red/Wht

Temp. Range: -20 to 80°C

Min. Bend Radius : 1.2 inches

Ripcord : RIPCORDER

Outer Jacket : PVC

Certification and Approvals : CSA C22.2 No 214/UL 444 CSA C22.2 No 210

Print Notes : Seq. marked in Meters (0 - putup length) RESET

Standard Print : LOW CAP CSA-C/US CMG 75°C LL61365 OR CSA AWM II A 80°C 150V FT4
LOW VOLTAGE COMPUTER CABLE 22 AWG ROHS
WWW.CERCOCABLE.COM 8247 AT-HOM 29 A B C D E F G H
I J

Electrical Characteristics :

DC Resistance 25°C: 24.3 Ohms / 1000 ft

Mutual Capacitance : 12.5 pF/ft

Cond to Shield Cap. : 4.9 pF/ft

Impedance : 100 Ohms

Inductance. : 1.4 mH/km

All Cables are Canadian Made in Ontario

QMS Registered ISO 9001

Electro Cables Inc. has been manufacturing quality cables for over 35 years.

(All of the above values are approximated to within +/- 10%)

5302251TFT4.AH