



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896

Fax: 613-394-4101 email: sales@electrocables.com

Mailing: P.O. Box 276, Trenton, ON K8V 5R5

www.electrocables.com

23-Jan-2023

Product Number : **5601856BFT4.AH**

RoHS

AT-HOM Individual Shielded 6/PR 18/16 AWG SBC

PO Insulation, Individual Shields, Overall Individual Drains, DARK ORANGE

PVC Jacket

General Specification of Product :

Final Diameter : 0.434 inches 11.024 mm

Total Cable Weight: 183.0 kg/km 123.0 lbs/1000 ft

Conductor : 18 AWG 16 Stranded Bare Copper

Insulation : 0.015" PO

Shield : Individual Shields Foil Free Mylar

Drain \ Ground: Individual Drains 22 AWG 7 Stranded Tinned Copper

Colour Code: Blk paired with Red,Rd/Wht,Blu/Wht,Rd/Blk,Rd/Blue,White

Temp. Range : -20 to 80°C

Min. Bend Radius: 3.0 inches

Ripcord : RIPCORDER

Outer Jacket : PVC

Print Notes : Seq. marked in Meters (0 - putup length) RESET

Standard Print : CSA-C/US CMG 75°C LL61365 OR CSA AWM II A/B 80°C 600V FT4 18 AWG
ROHS WWW.CERCOCABLE.COM 8254 AT-HOM 29 A B C D E F
G H I J

Electrical Characteristics :

DC Resistance 25°C: 6.8 Ohms / 1000 ft

Mutual Capacitance : 29 pF/ft

Cond to Shield Cap. : 51.4 pF/ft

Impedance : 55 Ohms

Inductance. : 1.4 mH/km

All Cables are Canadian Made in Ontario

QMS Registered ISO 9001

Electro Cables Inc. has been manufacturing quality cables for over 35 years.

(All of the above values are approximated to within +/- 10%)

5601856BFT4.AH