



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896

Fax: 613-394-4101 email: sales@electrocables.com

Mailing: P.O. Box 276, Trenton, ON K8V 5R5

www.electrocables.com

17-Apr-2023

Product Number : **6101851BPV6.10R.300**

RoHS

Unshielded Cable 1/PR 18/7 AWG SBC
CSA-C/US CMP FT6 75°C, CSA 600V AWM
PVC PLENUM Insulation
PVC PLENUM FT-6 Jacket

General Specification of Product :

Final Diameter : 0.158 inches 4.013 mm

Total Cable Weight: 27.0 kg/km 18.1 lbs/1000 ft

Conductor : 18 AWG 7 Stranded Bare Copper Conductor

Insulation : 0.008" PVC

Colour Code: Black paired with Red

Temp. Range : -20 to 75°C

Min. Bend Radius: 1.1 inches

Ripcord : RIPCORDER

Outer Jacket : PVC

Twists per Foot: 4

Certification and Approvals : CSA C22.2 No. 214/UL 444, CSA C22.2 No. 210

Print Notes : Sequentially marked in Meters (0 - infinity)

Standard Print : CSA-C/US CMP LL61365 75°C OR CSA AWM II A/B 75°C 600V FT6 1/PR 18
AWG ROHS WWW.CERCOCABLE.COM A B C D E F G H I
J

Electrical Characteristics :

DC Resistance 25°C: 6.8 Ohms / 1000 ft

Mutual Capacitance : 21.7 pF/ft

Impedance : 75 Ohms

Inductance. : 1.3 mH/km

All Cables are Canadian Made in Ontario

QMS Registered ISO 9001

Electro Cables Inc. has been manufacturing quality cables for over 35 years.

(All of the above values are approximated to within +/- 10%)

6101851BPV6.10R.300