



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896

Fax: 613-394-4101 email: sales@electrocables.com

Mailing: P.O. Box 276, Trenton, ON K8V 5R5

www.electrocables.com

11-Jun-2019

Product Number : **6101851TFT4**

RoHS

Unshielded Cable 1/PR 18/16 AWG Stranded Tin Copper
600V 105°C FT4 CSA
SR-PVC Insulation
PVC FT-4 Jacket
Operating Temperature: -20 to 105°C

General Specification of Product :

Final Diameter : 0.182 inches 4.623 mm

Total Cable Weight: 30 kg/km 20 lbs/1000 ft

Conductor : 18 AWG 16 Strand Tinned Copper Conductor

Insulation : SR-PVC

Outer Jacket : PVC

Outdoor Rating : Sunlight Resistant

Print Notes :

Standard Print : ECI ELECTROCOM CSA CMG 105°C SUN RES LL61365 OR CSA AWM II A/B
105°C 600V FT4 (UL) CMG E132883 105°C #18 AWG ROHS

Electrical Characteristics :

DC Resistance 25°C: 6.8 Ohms / 1000 ft

Mutual Capacitance : 21.5 pF/ft

Impedance : 85 Ohms

Velocity of Prop : 68 %

Inductance. : 1.3 mH/km

Additional Information :

Please contact Sales regarding Finished Lengths, Insulation and Jacket Colours.

All Cables are Canadian Made in Ontario

QMS Registered ISO 9001

Electro Cables Inc. has been manufacturing quality cables for over 30 years.

(All of the above values are approximated to within +/- 10%)

6101851TFT4