



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896

Fax: 613-394-4101 email: sales@electrocables.com

Mailing: P.O. Box 276, Trenton, ON K8V 5R5

www.electrocables.com

27-Jan-2023

Product Number : **6111810BPV6**

RoHS

Unshielded Cable FT6 10/C 18/1 AWG SBC

CSA-C/US CMP FT6 75°C, CSA 300V AWM

PVC Insulation

PVC Jacket

General Specification of Product :

Final Diameter : 0.235 inches 5.969 mm

Total Cable Weight: 104.0 kg/km 69.9 lbs/1000 ft

Conductor : 18 AWG Solid Bare Copper

Insulation : PVC

Colour Code: Blk,Wht,Red,Grn,Org,Blue,Ylw,Brn,Pur,Gry

Temp. Range : -20 to 75°C

Min. Bend Radius : 1.6 inches

Ripcord : RIPCORDER

Outer Jacket : PVC

Certification and Approvals : CSA C22.2 No. 214/UL 444, CSA C22.2 No. 210

Print Notes :

Standard Print : CSA-C/US CMP LL61365 75°C OR CSA AWM II A/B 75°C 300V FT6 10/C 18
AWG ROHS WWW.CERCOCABLE.COM A B C D E F G H I
J

Electrical Characteristics :

DC Resistance 25°C: 6.5 Ohms / 1000 ft

Mutual Capacitance : 27.8 pF/ft

Impedance : 70 Ohms

Inductance. : 1.4 mH/km

All Cables are Canadian Made in Ontario

QMS Registered ISO 9001

Electro Cables Inc. has been manufacturing quality cables for over 35 years.

(All of the above values are approximated to within +/- 10%)

6111810BPV6