

Date:

14-Nov-24

Product Number: **7201405BAR4.R**



CSA FAS105 ELECTRALERT Fire Alarm Cable - 300V 105C FT4

5/C 14 AWG Solid Bare Copper -ASTM B3

Polyvinyl Chloride (PVC) Insulation

Red- Polyvinyl Chloride(PVC) Inner Jacket

Red Coated - Aluminum Interlock Armour (AIA)

Temperature Rating -30°C to 105°C

General Specification of Product :

Final Diameter :	0.479 inches	12.2 mm
Total Cable Weight :	119 lbs/1000 ft	176 kg/km
Conductor :	14 AWG Solid Bare Copper ASTM B3	
Insulation :	Polyvinyl Chloride (PVC) Colour Code # 7	0.015 inches 0.4 mm
Shielding:	Unshielded	
Inner Jacket	Red - Polyvinyl Chloride(PVC) Inner Jacket	
Ripcord:	Ripcord included	
Armour	Red Coated - Aluminum Interlock Armour (AIA)	

lay Length: ≥ 3.0"

Outdoor Rating : Sunlight Resistant

Certification and Approvals : CSA C22.2 No. 208, Fire alarm and signal cable (Type FAS105)

CSA C22.2 No. 2556, FT4 Vertical-Tray Flame Test

Print Notes : ECI ELECTRALERT FIRE ALARM & SIGNAL CABLE FAS105 300 VOLTS

SUN RES CSA LL61365 FT4 5/C 14 AWG

RoHS [Work Order No.]

Electrical Characteristics :		Physical Characteristics :	
DC Resistance 20°C :	2.628 Ω/1000ft (8.62 Ω/km)	Maximum Pulling Tension :	164 lbs / 75 kg
Inductance:	0.131 pH/ft	Minimum Bend Radius - Pulling :	5.7 in. / 146 mm
Impedance:	73.364 Ohms	Minimum Bend Radius - Permanent :	4.8 in. / 122 mm
Capacitance"	24.4 pF/ft		

Temperature :

Handling and Installation : -10°C to +105°C

Operation and Storage : -30°C to +105°C

Appropriate precautions should be taken for all installations below -10°C. Please consult Electro Cables for additional handling and installation instructions for cables exposed to lower ambient temperatures.

Fire Hazard Performance :

CSA C22.2 No. 2556 Method 2 - FT4 Vertical Flame Test

All Cables are Canadian Made in Ontario

Spec Tolerance of +/- 10% on all values

QMS Registered ISO 9001

UNCONTROLLED COPY

(All of the above values are approximated to within ±15%)

ElectroSIM R35

11/14/2024 11:59 AM