



# SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896

Fax: 613-394-4101 email: sales@electrocables.com

Mailing: P.O. Box 276, Trenton, ON K8V 5R5

www.electrocables.com

6-Jan-2023

Product Number : **6101603BFT4.AH**

RoHS

AT-HOM Unshielded Cable 3/C 16/7 AWG SBC

CSA (UL) CMG FT4 105°C, CSA 600V AWM

PVC Insulation

DARK ORANGE PVC Jacket

## General Specification of Product :

Final Diameter : 0.240 inches 6.096 mm

Total Cable Weight: 69.0 kg/km 46.4 lbs/1000 ft

Conductor : 16 AWG 7 Stranded Bare Copper

Insulation : 0.015" SR-PVC

Colour Code: Black / Red/White / Blue/White

Temp. Range: -20° to 105°C

Min. Bend Radius: 1.7 inches

Ripcord : RIPCORDER

Outer Jacket : PVC

Outdoor Rating : Sunlight Resistant

Certification and Approvals : CSA C22.2 No. 214/UL 444, CSA C22.2 No. 210

Print Notes : Seq. marked in Meters (0 - putup length) RESET

Standard Print : CSA CMG 105°C SUN RES LL61365 OR CSA AWM II A/B 105°C 600V FT4  
(UL) CMG E132883 105°C #16 AWG ROHS WWW.CERCOCABLES.COM 8191  
AT-HOM 29 A B C D E F G H I J

## Electrical Characteristics :

DC Resistance 25°C: 4.3 Ohms / 1000 ft

Mutual Capacitance : 20.6 pF/ft

Impedance : 80 Ohms

Inductance. : 1.4 mH/km

All Cables are Canadian Made in Ontario

QMS Registered ISO 9001

Electro Cables Inc. has been manufacturing quality cables for over 35 years.

( All of the above values are approximated to within +/- 10% )

6101603BFT4.AH