



# SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896

Fax: 613-394-4101 email: sales@electrocables.com

Mailing: P.O. Box 276, Trenton, ON K8V 5R5

www.electrocables.com

6-Jan-2023

Product Number : **5152204TFT4.AH**

RoHS

AT-HOM Overall Shielded Cable 4/C 22/7 AWG STC

CSA (UL) CMG FT4 105°C, CSA 600V AWM

PVC Insulation, DARK ORANGE PVC Jacket

## General Specification of Product :

Final Diameter : 0.163 inches 4.140 mm

Total Cable Weight: 31.0 kg/km 20.8 lbs/1000 ft

Conductor : 22 AWG 7 Stranded Tinned Copper

Insulation : 0.010" PVC

Shield : Overall Foil Shield

Drain \ Ground: 24 AWG 7 Stranded Tinned Copper

Colour Code: Black / White / Red / Green

Temp. Range : -20 to 105°C

Min. Bend Radius: 1.1 inches

Ripcord : RIPCORDER

Outer Jacket : PVC

Outdoor Rating : Sunlight Resistant

Certification and Approvals : CSA C22.2 No. 214/UL 444, CSA C22.2 No. 210

Print Notes : Seq. marked in Meters (0 - putup length) RESET

Standard Print : CSA CMG 105°C SUN RES LL61365 OR CSA AWM II A/B 105°C 600V FT4  
(UL) CMG E132883 105°C #22 AWG PS-C\$ WWW.CERCOCABLE.COM 8242  
AT-HOM 29 THERMOCOM A B C D E F G H I J

## Electrical Characteristics :

DC Resistance 25°C: 17.9 Ohms / 1000 ft

Mutual Capacitance : 36 pF/ft

Cond to Shield Cap. : 65 pF/ft

Impedance : 60 Ohms

Inductance. : 1.3 mH/km

All Cables are Canadian Made in Ontario

QMS Registered ISO 9001

Electro Cables Inc. has been manufacturing quality cables for over 35 years.

( All of the above values are approximated to within +/- 10% )

5152204TFT4.AH