



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896

Fax: 613-394-4101 email: sales@electrocables.com

Mailing: P.O. Box 276, Trenton, ON K8V 5R5

www.electrocables.com

6-Jan-2023

Product Number : **6101603BPV6.AH**

RoHS

AT-HOM Unshielded Cable 3/C 16/19 AWG SBC
CSA-C/US CMP FT6 75°C, CSA 300V AWM
PVC Insulation
DARK ORANGE PVC Jacket

General Specification of Product :

Final Diameter :	0.196 inches	4.978 mm
Total Cable Weight:	57.0 kg/km	38.3 lbs/1000 ft
Conductor :	16 AWG 19 Strand Bare Copper	
Insulation :	0.010" PVC	
Colour Code:	Black / Red/White / Blue/White	
Temp. Range :	-20 to 75°C	
Min. Bend Radius :	1.4 inches	
Ripcord :	RIPCORDER	
Outer Jacket :	PVC	

Certification and Approvals : CSA C22.2 No. 214/UL 444, CSA C22.2 No. 210

Print Notes : Seq. marked in Meters (0 - putup length) RESET

Standard Print : CSA-C/US CMP LL61365 75°C OR CSA AWM II A/B 75°C 300V FT6 3/C 16
AWG ROHS WWW.CERCOCABLE.COM 8261 AT-HOM 29 A B C D
E F G H I J

Electrical Characteristics :

DC Resistance 25°C:	4.3 Ohms / 1000 ft
Mutual Capacitance :	26.2 pF/ft
Impedance :	70 Ohms
Inductance. :	1.4 mH/km

All Cables are Canadian Made in Ontario

QMS Registered ISO 9001

Electro Cables Inc. has been manufacturing quality cables for over 35 years.

(All of the above values are approximated to within +/- 10%)

6101603BPV6.AH