



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896

Fax: 613-394-4101 email: sales@electrocables.com

Mailing: P.O. Box 276, Trenton, ON K8V 5R5

www.electrocables.com

6-Jan-2023

Product Number : **6101803BPV6.AH**

RoHS

AT-HOM Unshielded Cable 3/C 18/7 AWG SBC

CSA-C/US CMP FT6 75°C, CSA 300V AWM

PVC Insulation

DARK ORANGE PVC Jacket

General Specification of Product :

Final Diameter : 0.168 inches 4.267 mm

Total Cable Weight: 40.0 kg/km 26.9 lbs/1000 ft

Conductor : 18 AWG 7 Stranded Bare Copper

Insulation : 0.008" PVC

Colour Code : Black / Red/White / Blue/White

Temp. Range: -20 to 75°C

Min. Bend Radius: 1.2 inches

Ripcord : RIPCORDER

Outer Jacket : PVC

Certification and Approvals : CSA C22.2 No. 214/UL 444, CSA C22.2 No. 210

Print Notes : Seq. marked in Meters (0 - putup length) Reset

Standard Print : CSA-C/US CMP LL61365 75°C OR CSA AWM II A/B 75°C 300V FT6 3/C 18
AWG ROHS WWW.CERCOCABLE.COM 8271 AT-HOM 29 A B C D
E F G H I J

Electrical Characteristics :

DC Resistance 25°C: 6.8 Ohms / 1000 ft

Mutual Capacitance : 24.8 pF/ft

Impedance : 80 Ohms

Inductance. : 1.3 mH/km

All Cables are Canadian Made in Ontario

QMS Registered ISO 9001

Electro Cables Inc. has been manufacturing quality cables for over 35 years.

(All of the above values are approximated to within +/- 10%)

6101803BPV6.AH