



8287

529 Thomas Drive, Bensenville, IL 60106 | TF: 888.518.8086 | FX: 630.860.5944

Specification Sheet

Lake Cable Part #: P162CS/X-03CERCO

Description: 16 AWG 2 conductors 19 strands bare copper wire, plenum rated PVC insulation, Shielded, with an overall plenum rated PVC jacket.

1. Conductor

- 1.1. AWG Size & Stranding: 16 AWG 19 Strands Class C
- 1.2. Material: Annealed Bare Copper
- 1.3. Conductor Count: 2 Conductors

2. Insulation

- 2.1. Material: Plenum Rated Polyvinylchloride
- 2.2. Wall Thickness: 0.007"
- 2.3. Diameter: 0.070" $\pm$ 0.002"
- 2.4. Color Code: Black & Red/White

3. Assembly

- 3.1. Nominal Lay Length: 3.00" LHL (4.00 Tw/Ft)
- 3.2. Shield: Aluminum Mylar Tape - 100% Coverage
- 3.3. Drain Wire: 20 AWG 10 Strand Tinned Copper

4. Jacket

- 4.1. Material: Plenum Rated Polyvinylchloride
- 4.2. Wall Thickness: 0.015"
- 4.3. Diameter: 0.172" $\pm$ 0.015"
- 4.4. Color: Orange
- 4.5. Ripcord: Yes
- 4.6. Weight: 29 Lbs/Mft

5. Markings

- 5.1. Type: Cable permanently identified via surface inkjet print
- 5.2. Legend: CERCO CABLE E171202 WWW.CERCOABLE.COM 16AWG 1PAIR SHIELDED 75C (UL) CL3P OR FPLP OR C(UL)US CMP FT6 MADE IN USA AT-HOM 29 #8287 "ROHS COMPLIANT"
- 5.3. Footage Markers: Yes, Ascending/Descending

7. Standards

- 7.1. Cable suitable for installation under NEC (NFPA 70) articles 800, 725 and 760 guidelines
- 7.2. Cable suitable for installation in Canada under Section 60 of CEC, Part I
- 7.3. C(UL)US listed as CMP per UL standard 444 and per CSA C22.2 No. 214-17
- 7.4. UL listed as CL3P per UL standard 13 or FPLP per UL standard 1424
- 7.5. Cable meets NFPA 262 (Steiner tunnel) flame test
- 7.6. Cable meets RoHS 2002/95/EC Directive, RoHS 2 2011/65/EU Directive, RoHS 3 2015/863/EU Directive
- 7.7. Cable is REACH compliant per Regulation (EC) No 1907/2006 (223) Updated January 17, 2022
- 7.8. Operating Voltage: Maximum 300V RMS
- 7.9. Made in the USA
- 7.10. **WARNING:** This product may contain chemicals, such as Vinyl Chloride, known to the state of California to cause cancer. For more information, go to www.P65Warnings.ca.gov. Wash hands after handling

ALL SPECIFIED PARAMETERS WITHOUT A TOLERANCE ARE NOMINAL AND SUBJECT TO VERIFICATION. LAKE CABLE IS NOT RESPONSIBLE FOR UNKNOWN PERFORMANCE ATTRIBUTES THAT WERE NOT MADE KNOWN TO LAKE CABLE AT THE TIME OF DESIGN.

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

[Signature]
Signature

CERCO CABLE
Company

Sept 21 - 2022
Date