



# SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896

Fax: 613-394-4101 email: sales@electrocables.com

Mailing: P.O. Box 276, Trenton, ON K8V 5R5

www.electrocables.com

6-Jan-2023

Product Number : **5152051BPV6.AH**

RoHS

AT-HOM Overall Shielded Cable 1/PR 20/7 AWG SBC

CSA-C/US CMP FT6 75°C, CSA 300V AWM

PVC Insulation, DARK ORANGE PVC Jacket

## General Specification of Product :

Final Diameter : 0.140 inches 3.556 mm

Total Cable Weight: 23.0 kg/km 15.5 lbs/1000 ft

Conductor : 20 AWG 7 Stranded Bare Copper

Insulation : PVC

Shield : Overall Shield

Drain \ Ground: 24 AWG 7 Strand Tinned Copper

Colour Code: Black / Red/White

Temp. Range: -20 to 75°C

Min. Bend Radius : 1.0 inches

Outer Jacket : PVC

Certification and Approvals : CSA C22.2 No. 214/UL 444, CSA C22.2 No. 210

Print Notes : Seq. marked in Meters (0 - putup length) RESET

Standard Print : CSA-C/US CMP LL61365 75°C OR CSA AWM II A/B 75°C 300V FT6 1/PR 20  
AWG WWW.CERCOCABLE.COM 8300 AT-HOM 29 A B C D E  
F G H I J

## Electrical Characteristics :

DC Resistance 25°C: 10.7 Ohms / 1000 ft

Mutual Capacitance : 52.7 pF/ft

Cond to Shield Cap. : 94.2 pF/ft

Impedance : 55 Ohms

Inductance. : 1.4 mH/km

All Cables are Canadian Made in Ontario

QMS Registered ISO 9001

Electro Cables Inc. has been manufacturing quality cables for over 35 years.

( All of the above values are approximated to within +/- 10% )

5152051BPV6.AH