



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896

Fax: 613-394-4101 email: sales@electrocables.com

Mailing: P.O. Box 276, Trenton, ON K8V 5R5

www.electrocables.com

17-Jul-2023

Product Number : **9000157TFT4**

RoHS

Composite Cable

SH 6/PR 22/7 STC 0.010" SR-PVC INS,

SH 2/PR 16/26 STC 0.015" SR-PVC INS, 18/16 STC DRAIN

FOIL AND DRAIN FACING IN & O/A 0.040" PVC JKT FT4;

General Specification of Product :

Final Diameter : 0.480 inches 12.192 mm

Total Cable Weight: 190.0 kg/km 127.7 lbs/1000 ft

Insulation : SR-PVC

Twists per Foot : 2.4

Outer Jacket : 0.040" PVC

Print Notes : Seq. marked in Meters (0 - infinity)

Standard Print : CSA CMG 105°C LL61365 OR CSA AWM II A/B 105°C 600V FT4 (UL) CMG
E132883 105°C 6PR 22 AWG 2PR 16 AWG WWW.CERCOCABLE.COM A B C
D E F G H I J ROHS

Additional Information :

SH 6/PR 22/7

DC Resistance: 25°C 17.5

Ohms/1000' Cond. Shld Capacitance:

46.4pF/ft Mutual Capacitance: 25.9 pF/

ft Impedance: 100 Ohms

Velocity of Prop: 60%

Inductance: 1.3 (mH/km)

SH. 2/PR 16/26

DC Resistance: 25°C 4.2 Ohms/1000

Cond. Shld Capacitance: 68.6pF/ft

Mutual Capacitance: 38 pF/ft

Impedance: 70 (Ohms)

Velocity of Prop: 60%

Inductance: 1.2 mH/km)

All Cables are Canadian Made in Ontario

QMS Registered ISO 9001

Electro Cables Inc. has been manufacturing quality cables for over 35 years.

(All of the above values are approximated to within +/- 10%)

9000157TFT4