



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896

Fax: 613-394-4101 email: sales@electrocables.com

Mailing: P.O. Box 276, Trenton, ON K8V 5R5

www.electrocables.com

19-Jun-2024

Product Number : **6501404BPLTC.01S.75**

RoHS

Unshielded PLTC Cable 4/C 14/7 AWG SBC

300V 105°C FT4 CSA

PVC Insulation, PVC Jacket

General Specification of Product :

Final Diameter : 0.326 inches 8.280 mm

Total Cable Weight: 148.0 kg/km 98.1 lbs/1000 ft

Conductor : 14 AWG 7 Stranded Bare Copper

Insulation : PVC

Temp. Range : -20 to 105°C

Colour Code: Black,White,Red,Green

Min. Bend Radius : 2.3 inches

Twists per Foot: 2.6

Ripcord : RIPCORDER

Outer Jacket : PVC

Outdoor Rating : Sunlight Resistant

Print Notes :

Standard Print : ECI CSA AWM II A/B FT4 LL61365 105°C 300V (UL) E132885 PLTC 105°C 14 AWG SUN RES ROHS

Electrical Characteristics :

DC Resistance 25°C: 2.6 Ohms / 1000 ft

Mutual Capacitance : 22.9 pF/ft

Impedance : 70 Ohms

Inductance. : 1.2 mH/km

All Cables are Canadian Made in Ontario

QMS Registered ISO 9001

Electro Cables Inc. has been manufacturing quality cables for over 35 years.

(All of the above values are approximated to within +/- 10%)

6501404BPLTC.01S.75