



Domtech Inc.
40 East Davis Street
Trenton, Ontario
Canada, K8V 6S4
Ph: 613-394-4884
Fax: 613-394-5372
Toll Free: 888-278-8258 (USA & Canada)
www.domtech.net

PRODUCT SPECIFICATION

February 12, 2025

PART NUMBER: 3818273

DESCRIPTION: Q-ELEFT4 NIPLL 18(1B)/2 105C BROWN
.094"X.153",CC008(BLK-WHT,SRPVC)BLK-INK,PS808,CMG/CM/PJT/AWM
FT1/FT4/VW-1,UL/CSA, 6.5X3X2 MTL SPOOL,75M(246FT)

CONDUCTOR: Solid #18 awg .0403" soft bare copper

INSULATION: SRPVC, .008" nominal thickness, .059" +/- .002" diameter

ASSEMBLY: Parallel, non-integral conductors
Polyester ripcord applied between the insulated conductor and the jacket.

COLOUR SEQUENCE: Black-White

JACKET: PVC, .015" nominal thickness
DIAMETER: .094" +/- .010" x .153" +/- .010"

PRINT TYPE: Non-contact, sequential (Black ink)
PRINT LEGEND: c-CSA-us CMG OR CM OR CMX Outdoor 18AWG 105C
OR CSA AWM I/II A/B 105C 600V FT1 FT4 VW-1 LL39965 ---- UL CM 18AWG 105C
NOTE: Sequential print is available as requested by the customer in foot or meter
markings

TEMPERATURE: -20°C to 105°C

VOLTAGE: 300 V

FLAME RATING: FT1/ FT4/ VW-1

SPECIFICATION : CSA C22.2 No. 214 & 210
UL444

APPROVALS: CSA FILE NUMBER LL39965
UL FILE NUMBER E132773
RoHS Compliant